

Tradesman Buff Multi Best A0304A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4


Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.**

U for use in Unprotected Masonry

Registered Office
Ibstock Brick Limited, Leicester Road, Ibstock Leicestershire, LE67 6HS

Attestation of conformity **System 2+**

Notified factory production certification body 1855 .CPR/24536 **Lucideon CICS Limited** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

| Declared Performance Essential Characteristics | Performance | | Harmonised Technical Specification |
|--|-----------------------|-------|---|
| Dimensions & tolerance mm | 215x102x65 | | BS EN 771-1:2011+A1:2015 The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by: Andy Batterham - Technical Director Ibstock Brick Limited  |
| | Tolerance | T2 | |
| | Range | R1 | |
| Configuration | Vertically Perforated | | |
| Compressive Strength (tested normal to the bed face of the unit) N/mm ² | Mean | 60 | |
| | Normalised | 51 | |
| | Category | Cat I | |
| Dimensional Stability mm/m ³ | NPD | | |
| Bond Strength fixed N/mm ² | 0.15 | | |
| Active Soluble Salts | S2 | | |
| Reaction to Fire | Euro Class A1 | | Comission decision 2000/605/EC |
| Water absorption % | 9 | | BS EN 771-1:2011+A1:2015 |
| Water Vapour Permeability | 50/100 | | |
| Direct Airbourne sound insulation Kg/m ³ (Gross) | 1550 | | |
| Thermal Conductivity W/mk | 1.15 | | |
| Durability against freeze thaw | F2~ | | |
| Dangerous Substances | NPD | | |