

Tradesman Heather Mixture 73mm Best C0381A


Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.**

U for use in Unprotected Masonry

Registered Office
Ibstock Brick Limited, Leicester Road, Ibstock Leicestershire, LE67 6HS

Attestation of conformity 4

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification
Dimensions & tolerance mm	215x102x73		BS EN 771-1:2011+A1:2015 The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by: Andy Batterham - Technical Director Ibstock Brick Limited 
	Tolerance	T2	
	Range	R1	
Configuration	Vertically Perforated		
Compressive Strength (tested normal to the bed face of the unit) N/mm ²	Mean	60	
	Normalised	63.4	
	Category	Cat II	
Dimensional Stability mm/m ³	NPD		
Bond Strength fixed N/mm ²	0.15		
Active Soluble Salts	S2		
Reaction to Fire	Euro Class A1		Comission decision 2000/605/EC
Water absorption %	9		BS EN 771-1:2011+A1:2015
Water Vapour Permeability	50/100		
Direct Airbourne sound insulation Kg/m ³ (Gross)	1660		
Thermal Conductivity W/mk	1.16		
Durability against freeze thaw	F2~		
Dangerous Substances	NPD		

Data correct since: 18/12/19
 For data prior to this date, please contact technical@ibstock.co.uk
 Downloaded: 12/11/2020