

TerraTrack Lite

TerraTrack Lite Nonwoven Geotextile



CE

DESCRIPTION

TerraTrack Lite Nonwoven Geotextile

SPECIFICATION

General information

Stock code	GTERRALITE
Range	TerraTrack
Third party certified	CE
Roll sizes	1m x 14m 2.25m x 25m 2.25m x 50m

Geotextile properties

Material	Polypropylene	
Tensile strength (MD)	EN ISO 10319	6.5kN/m
Tensile strength (CMD)	EN ISO 10319	6.9kN/m
Elongation at max load (MD)	EN ISO 10319	50%
Elongation at max load (CMD)	EN ISO 10319	65%
Dynamic perforation resistance	EN ISO 13433	38mm
CBR puncture resistance	EN ISO 12236	1100N

Dynamic cone drop	EN ISO 13433	38mm
Predicted minimum durability		100 years
Water permeability	EN ISO 11058	120L/m ² .s
Characteristic opening size	EN ISO 12956	110µm
Permeability	EN ISO 11058	120L/m ² .s
Weight	EN ISO 9864	100g/m ²

1. Geoworks (trading as Wrekin Products Ltd.) continually seeks to improve its products and, therefore, reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Geoworks products are supplied subject to our [Terms and Conditions of Sale](#).

